

Jumper Wire



Application:

- In distribution frames and cabinets.

Cable Construction:

- 1 – Conductor: Class 1 electrolytic solid copper (TS 3544, IEC 60228, DIN VDE 0295, EN 60228)
- 2 - Insulation: UV resistant PVC insulation (BS 6746). RAL 5015 (Blue)/RAL 1016 (Yellow)
- 3 - Stranding: Insulations are stranded together

Technical Characteristics:

Conductor Diameter	Conductor Resistance Ω/km (20 °C)	Insulation Resistance $M\Omega/\text{km}$	Dielectric Strength V (DC. 1 minute)	Test Voltage V (DC. 1 minute)
0.50 mm	93	200	1000	1500
0.60 mm	64.6	200	1000	1500
0.80 mm	37	200	1000	1500



Mechanical Characteristics:

Bending Radius	Temperature Range Operating
7.5xD mm	-30°C ~ +70°C

Ordering Information

Part Number	Description
TL-TC-IND-0.5-01	0.5*1 pair Blue/Yellow Insulation Jumper Wire 500mtr/Roll
TL-TC-IND-0.6-01	0.6*1 pair Blue/Yellow Insulation Jumper Wire 500mtr/Roll
TL-TC-IND-0.8-01	0.8*1 pair Blue/Yellow Insulation Jumper Wire 500mtr/Roll

JUMPER WIRE